

ø (mm)

mafdel			2	3	4	5	6	7	8	9	9.5	10	12	12.5	15	18	
Standard	Rough	<b>POLY/FLEX</b> Rough	85 ShA	●	●	●	●	●	●	●		●	●		●		
		<b>POLY/FLEX</b> Rough	85 ShA		●	●	●	●		●			●				
	Smooth	<b>SOUPLEX</b>	85 ShA		●	●	●	●		●		●			●	●	●
		<b>SOUPLEX</b>	85 ShA		○	○	○	○									
		<b>DEL/FLEX</b>	90 ShA	●	●	●	●	●	●	●		●			●	●	●
		<b>DEL/FLEX</b>	90 ShA		●	●	●	●		●							
		<b>DEL/ROC</b>	100 ShA 55 ShD			●	●	●		●		○	●				
	Frosted	<b>SOUPLEX</b> Frosted	85 ShA					●		●		●			●	●	●
		<b>DEL/FLEX</b> Frosted	90 ShA					●	●	●		●			●	●	●
		<b>DEL/FLEX</b> Frosted	90 ShA					●		●							
Reinforced	Smooth	<b>POLY/FLEX</b> Aramid Reinforced	85 ShA				●		●			●	●		●	●	
		<b>DEL/SAN</b> Aramid Reinforced	95 ShA									●		●	●	●	
		<b>DEL/ROC</b> Polyester Reinforced	100 ShA 55 ShD									○	○		○	○	○
		<b>DEL/ROC "DRW"</b> Polyester Reinforced	63 ShD									○		○			
	Frosted	<b>POLY/FLEX</b> Aramid Reinforced - Frosted	85 ShA				●		●			●	●		●	●	
		<b>DEL/SAN</b> Aramid Reinforced - Frosted	95 ShA									●		●	●	●	
Tubular	<b>SOUPLEX</b> Tubular	85 ShA										○					
	<b>DEL/FLEX</b> Tubular	90 ShA				○	○		○			○	○		○		



All our 6 to 18mm diameter round belts can be frosted.

Frosting improves belt sliding on its support and makes products accumulation easier.



Patent nb 9912595