

Cross section (mm)

		mafdel		8 x 5	10 x 6	13 x 8	17 x 11	22 x 14	32 x 19	13 x 15	17 x 20	22 x 25
Standard	Non-reinforced	DEL/ROC	100 ShA 55 ShD									
		DEL/FLEX	90 ShA									
		DEL/FLEX	90 ShA									
		SOUPLEX	85 ShA									
	Reinforced	DEL/SAN Aramid reinforced	95 ShA									
		H15 / H16 Aramid reinforced	92 ShA									
SOUPLEX Aramid reinforced		85 ShA										
Ridge-Top	TOPGRIP	SOUPLEX Aramid reinforced	85 ShA									
		DEL/SAN Aramid reinforced	95 ShA									
		H15 / H16 Aramid reinforced	92 ShA									
		SOUPLEX Aramid reinforced	85 ShA									
		DEL/FLEX	90 ShA									
	SOUPLEX	85 ShA										




All V belts from 10 x 6 mm (Z) section can be cogged.
Cogging reduces minimum pulley diameter.




Coatings : from 10 x 6mm (Z) section
Wide range of smooth or textured coatings made of PU, PVC, felt, rubber.

standard surfaces


PU surfaces 85 ShA or 70 ShA



smooth



non-slip studded



saw-tooth




SG3 - fish bone




trellis



SUPERGRIP coatings



PVC



rubber