

BELTS

METAL DETECTABLE



CHARACTERISTICS:

- Single material belt, waterproof and rot-proof
- Resistant to water, detergents, animal and vegetable oils and fats
- EU marking
- Metal detectable
- Hardness: 90shA
- Temperatures range: +20°C/+70°C
- Coefficient of friction :
HDPE 0.25
Stainless steel 0.6

TRAPEZOIDAL BELTS - DEL/FLEX BLUE



plain



cogged

Reference	Traction force (daN)	ø pulley (mm)		Section	Tension	Reference	Traction force (daN)	ø pulley (mm)	
		Recommended	Mini					Recommended	Mini
DFVB08MD	6	55	50	8x5 (M)	5%	-	-	-	-
DFVB10MD	10	80	65	10x6 (Z)	5%	DFVBCR10MD	6	60	50
DFVB13MD	18	100	80	13x8 (A)	5%	DFVBCR13MD	13	80	60

From stock in 30 m rolls

ATC BELTS - 63 BLUE

Reference	Top face	Section	Pulling force (daN)	Tension	ø pulley (mm)	
					Recommended	Mini
ATC63BMD	structured	25x2.3 mm +	14	5%	60	50
ATC63BLIMD	smooth	guide 4x2.5mm	14	5%	60	50

From stock in 30 m rolls

ROUND BELTS- DEL/FLEX BLUE

Reference	Section (ø en mm)	Traction force (daN)	Tension	ø pulley at bottom of groove (mm)	
				Recommended	Mini
DFRB04MD	4	2.2	5%	40	30
DFRB05MD	5	3.5	5%	50	40
DFRB06MD	6	5.8	5%	60	50
DFRB08MD	8	11	5%	80	65

On request



mafdel

MAFDEL

Z.I. Lafayette - 131, rue de la Plaine
38790 Saint Georges d'Espérance - FRANCE
Tel. +33 (0)4 78 96 21 90 - mafdel@mafdel.fr
www.mafdel-belts.com

