



SOUPLEX ANTISTATIC



		SOUPLEX ANTISTATIC		
Reference		SXRN04AS	SXRN05AS	SXRN06AS
Color		Black		
Material		Polyurethane		
Cross-section \varnothing mm		4	5	6
Surface resistivity		10 ⁸ Ohms.m		
Tensile strength		1.5daN	2.5daN	4 daN
Tension		8%		
\varnothing Recommended Pulley (mm)		45	50	60
\varnothing Minimum pulley (mm)		35	40	50
Food Quality		No		
Tension		5 to 8 % depending on conditions		
Temperature range		-20°C / + 60°C		
Coefficient of friction	HDPE	0.35		
	Steel	0.60		
	Stainless steel	0.70		
Order quantity		30 m roll		



MAFDEL
 Z.I. Lafayette - 131, rue de la Plaine
 38790 Saint Georges d'Espérance - FRANCE
 Tel. +33 (0)4 78 96 21 90 - mafdel@mafdel.fr
www.mafdel-belts.com





DEL/FLEX ANTISTATIC



		DEL/FLEX ANTISTATIC	
References		DFP63AS	DFB63AS
Color		Dark green	
Material		Polyurethane	
Top side		Smooth	
Bottom side		Smooth	
Surface resistivity		10⁸ Ohms.m	
Thickness		3 mm	
Tensile strength		10 daN/cm ² cross section at 1% tension	
		15 daN/cm ² cross-section at 2% tension	
		20 daN/cm ² cross-section at 3% tension	
Maximum width		380 mm	
∅ Minimum rolling diameter		70 mm	
Weight		3.75 kg/m ²	
Tension		1 à 3 % depending on conditions	
Food Quality		No	
Extremes temperature		-20°C / + 70°C	
Coefficient of friction	HDPE	0.25	
	Steel	0.50	
	Stainless steel	0.60	



MAFDEL
 Z.I. Lafayette - 131, rue de la Plaine
 38790 Saint Georges d'Espéranche - FRANCE
 Tel. +33 (0)4 78 96 21 90 - mafdel@mafdel.fr
 www.mafdel-belts.com

